

SERIE 16

134A

AVO - Wheel with elastic rubber tyre and steel castor for industry,
diameter 150mm ean 28438

Material: Elastic Rubber
tyre

Core: Cast
Iron

Application field:
Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.
Hub on shielded ball bearings assembled with central space.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793284387

EAN5:28438

Article code:14134A015GECG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	45
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	/
Ground clearance (mm)	210
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted