

SERIE 16

45A

AVO - Wheel with elastic rubber tyre and steel castor for industry,
diameter 200mm ean 28429

Material: Elastic Rubber
tyre

Core: Cast
Iron

Application field:
Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.
Hub on shielded ball bearings assembled with central space.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793284295

EAN5:28429

Article code:14045A0200ECG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 600 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	600
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	/
Ground clearance (mm)	260
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted