

SERIE 16

## 45BISB

AVO - Wheel with elastic rubber tyre and steel castor for industry,  
diameter 200mm ean 28435

**Material:** Elastic Rubber tyre    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.  
Hub on shielded ball bearings assembled with central space.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

**Product line:** Rubber tyre

**EAN13:**8018793284356    **EAN5:**28435    **Article code:**14045BF200ECG



## Features

**Minimum temperature:** -20    **Maximum temperature:** 70    **Dynamic load capacity:** 600 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	600
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted