

SERIE 16

134

AVO - Wheel with elastic rubber tyre and steel castor for industry,
diameter 200mm ean 28437

Material: Elastic Rubber
tyre

Core: Cast
Iron

Application field:
Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.
Hub on shielded ball bearings assembled with central space.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered
roller bearings, with plate. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793284370

EAN5:28437

Article code:141340020GECG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 1200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1200
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	270
Castor hole (mm)	/
Static load capacity (DaN)	1500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted