Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

121

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 100mm ean 28442

Material: Mechanical Cast iron

Core: Cast Iron Application field: Industry

Indu

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793284424

EAN5:28442

Article code:0412100100GGP



Features Flooring

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 600 DaN

Asphalt

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

Concrete

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	600
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	60
Ground clearance (mm)	184
Castor hole (mm)	1
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted