Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

# **123BIS**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 100mm ean 28465

**Material:** Mechanical Cast iron

Core: Cast Iron

Application field:

Industry

#### Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

#### Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

**EAN13**:8018793284653 **EAN5**:28465

Article code:041230F100GGM



Features Flooring

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 600 DaN

AsphaltConcrete

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

### Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	600
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	60
Ground clearance (mm)	184
Castor hole (mm)	1
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	1
Finishing	Black painted