Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

121A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 28451

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 2200 DaN • Asphalt • Concrete

Rotation: Ball bearing Hardness scale: HB Hardness: 200

Wheel data

Diameter (mm)	200
Band width (mm)	48
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	2200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	1
Ground clearance (mm)	270
Castor hole (mm)	1
Static load capacity (DaN)	2750
Structure	Fixed
Version	1
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted