

SERIE 114A

121BIS

AVO - Wheel with mechanical cast iron and steel castor for industry,
diameter 200mm ean 28456

Material: Mechanical Cast iron **Core:** Cast Iron **Scope:** Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793284561 **EAN5:**28456 **Article code:**041210F200GGP



Features

Minimum temperature: -20 **Maximum temperature:** 120 **Dynamic load capacity:** 2200 DaN
Rotation: Ball bearing **Hardness scale:** HB **Hardness:** 200

Flooring

- Asphalt
- Concrete

Wheel data

| | |
|-----------------------------|----------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 48 |
| Hub width (mm) | 48 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 2200 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | / |
| Hardness scale | HB |
| Hardness | 200 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 200X200 |
| Plate hole spacing (mm) | 160X160 |
| Plate hole size (mm) | 17 |
| Offset (mm) | 72 |
| Ground clearance (mm) | 270 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 2750 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |