Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 114

123A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 28464

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 1200 DaN • Asphalt

Rotation: Ball bearing Hardness scale: HB Hardness: 200

Concrete

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	1200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	1
Ground clearance (mm)	270
Castor hole (mm)	1
Static load capacity (DaN)	1500
Structure	Fixed
Version	1
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted