

SERIE 180X

## 250XBIS

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 50mm ean 23394

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

**Furniture Castors:**

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate, front brake and locking device to stop both wheel and rotation.

**Product line:** Stainless steel

**EAN13:**8018793233941 **EAN5:**23394 **Article code:**222500F050XOG



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 40 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

### Wheel data

Diameter (mm)	50
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	40
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

### Support data

Plate size (mm)	060X060
Plate hole spacing (mm)	042X042
Plate hole size (mm)	6,5X10
Offset (mm)	30
Ground clearance (mm)	75
Castor hole (mm)	/
Static load capacity (DaN)	60
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel