

SERIE 180X

## 250XBISB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 60mm ean 24042

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material.

**Furniture Castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem, front brake and locking device to stop both wheel and rotation.

**Product line:** Stainless steel

**EAN13:**8018793240420 **EAN5:**24042 **Article code:**22250BF060X5G



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 50 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

### Wheel data

Diameter (mm)	60
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	27
Ground clearance (mm)	88
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Threaded axle
Finishing	AISI 304 stainless steel