

SERIE 180X

250XBISB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 75mm ean 27969

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

Furniture Castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem, front brake and locking device to stop both wheel and rotation.

Product line: Stainless steel

EAN13:8018793279697 **EAN5:**27969 **Article code:**22250BF075X5G



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 55 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

Diameter (mm)	75
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	55
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	27
Ground clearance (mm)	103
Castor hole (mm)	/
Static load capacity (DaN)	75
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Threaded axle
Finishing	AISI 304 stainless steel