

SERIE 139L

# 140LXA

**AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 80mm ean 28905**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, fixed.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793289054    **EAN5:**28905    **Article code:**06140A0080LCX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 75 DaN

**Rotation:** Stainless steel ball bearing

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	80
<b>Band width (mm)</b>	30
<b>Hub width (mm)</b>	40
<b>Hub version</b>	Stainless steel ball bearing
<b>Wheel hole (mm)</b>	8
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	75
<b>Colour</b>	Grey
<b>Material</b>	Non-marking Rubber tyre
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	85

## Support data

<b>Plate size (mm)</b>	100X085
<b>Plate hole spacing (mm)</b>	080X060
<b>Plate hole size (mm)</b>	8,5X12
<b>Offset (mm)</b>	/
<b>Ground clearance (mm)</b>	105
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	95
<b>Structure</b>	Fixed
<b>Version</b>	/
<b>Brake</b>	/
<b>Plain axle</b>	/
<b>Stem type</b>	/
<b>Finishing</b>	AISI 304 stainless steel