

SERIE 157-AM

# 157F-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for furniture, diameter 100mm ean 02104**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Furniture

**Description:**

Grey synthetic rubber wheel with thread guards and black thermoplastic centre. Pressed steel swivel bracket, zinc-plated, with double ball race. Bolted axle. Recommended for use on furniture and hospital equipment, metal furniture, household appliances, etc.

**Furniture Castors:**

**Product line:** Furniture

**EAN13:**8018793021043 **EAN5:**02104 **Article code:**SC157F010000G



## Features

**Minimum temperature:** / **Maximum temperature:** / **Dynamic load capacity:** 60 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

- Stoneware
- Wood

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 100                     |
| Band width (mm)             | 24                      |
| Hub width (mm)              | 34                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 12                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 60                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | 4                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 85                      |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | /          |
| Plate hole spacing (mm)    | /          |
| Plate hole size (mm)       | /          |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 128        |
| Castor hole (mm)           | 12,20      |
| Static load capacity (DaN) | 80         |
| Structure                  | Swivel     |
| Version                    | Bolt hole  |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |