

SERIE 154-AM

# 154BISB-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for furniture, diameter 80mm ean 12075**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Furniture

**Description:**

Grey synthetic rubber wheel with thread guards, black thermoplastic centre, bolted axle and pressed steel swivel bracket with ball race, chrome-plated or black painted, available with total lock (wheel and swivel lock). Recommended for use on furniture and hospital equipment, metal furniture, household appliances, etc.

**Furniture Castors:**

**Product line:** Furniture

**EAN13:**8018793120753

**EAN5:**12075

**Article code:**SC154BF080K6G



## Features

**Minimum temperature:** / **Maximum temperature:** / **Dynamic load capacity:** 60 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

- Stoneware
- Wood

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 80                      |
| Band width (mm)             | 23                      |
| Hub width (mm)              | 29                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 8                       |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 60                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | 4                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 85                      |

## Support data

|                            |                 |
|----------------------------|-----------------|
| Plate size (mm)            | /               |
| Plate hole spacing (mm)    | /               |
| Plate hole size (mm)       | /               |
| Offset (mm)                | /               |
| Ground clearance (mm)      | 115             |
| Castor hole (mm)           | /               |
| Static load capacity (DaN) | 80              |
| Structure                  | Swivel          |
| Version                    | Axle with brake |
| Brake                      | Front           |
| Plain axle                 | 12X30           |
| Stem type                  | Threaded axle   |
| Finishing                  | Black painted   |