

SERIE 139

140B

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 26930

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Rubber tyre

EAN13:8018793269308 **EAN5:**26930 **Article code:**06140B01250FG



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 105 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	/
Static load capacity (DaN)	125
Structure	Swivel
Version	Axle
Brake	/
Plain axle	20X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized