

SERIE 112AM

# 103F-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 140mm ean 28888

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793288880

**EAN5:**28888

**Article code:**03103F01400RG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 115 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	140
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	115
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	173
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized