

SERIE 139

# 140

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 150mm ean 29064**

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793290647 **EAN5:**29064 **Article code:**06140001500FG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 130 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	130
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	45
Ground clearance (mm)	179
Castor hole (mm)	/
Static load capacity (DaN)	160
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized