

SERIE 604-AM

## 605-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 250mm ean 29192

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

**Twin Wheel Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

**Product line:** Rubber tyre

**EAN13:**8018793291927    **EAN5:**29192    **Article code:**216050025008G



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 1350 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 70

### Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

### Wheel data

Diameter (mm)	250
Band width (mm)	84
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	1350
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

### Support data

Plate size (mm)	175X140
Plate hole spacing (mm)	140X105
Plate hole size (mm)	15
Offset (mm)	80
Ground clearance (mm)	305
Castor hole (mm)	/
Static load capacity (DaN)	1700
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted