

SERIE 604-AM

607-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 250mm ean 29211

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793292115 **EAN5:**29211 **Article code:**216070025008G



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 900 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------------|
| Diameter (mm) | 250 |
| Band width (mm) | 84 |
| Hub width (mm) | 75 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 900 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 70 |

Support data

| | |
|----------------------------|---------------|
| Plate size (mm) | 230X230 |
| Plate hole spacing (mm) | 190X190 |
| Plate hole size (mm) | 19 |
| Offset (mm) | 75 |
| Ground clearance (mm) | 305 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 1100 |
| Structure | Swivel |
| Version | Plate |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |