

SERIE 604-AM

606-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 406mm ean 29203

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793292030 **EAN5:**29203 **Article code:**216060040611G



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 950 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	406
Band width (mm)	104
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	950
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	250X250
Plate hole size (mm)	21
Offset (mm)	100
Ground clearance (mm)	535
Castor hole (mm)	/
Static load capacity (DaN)	1150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted