

SERIE 604-AM

## 606-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 457mm ean 29205

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

**Product line:** Rubber tyre

**EAN13:**8018793292054 **EAN5:**29205 **Article code:**216060045713G



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1400 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 70

## Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

## Wheel data

Diameter (mm)	457
Band width (mm)	122
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	1400
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

## Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	250X250
Plate hole size (mm)	21
Offset (mm)	100
Ground clearance (mm)	560
Castor hole (mm)	/
Static load capacity (DaN)	1750
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted