

SERIE 604-AM

## 604-AM

AVO - Wheel with non-marking rubber tyre for industry, diameter 250mm ean 29185

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

**Product line:** Rubber tyre

**EAN13:**8018793291859 **EAN5:**29185 **Article code:**146042525008G



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 450 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 70

### Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

### Wheel data

Diameter (mm)	250
Band width (mm)	84
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	47X12
Dynamic load capacity (DaN)	450
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/