

SERIE 604-AM

604-AM

AVO - Wheel with non-marking rubber tyre for industry, diameter 457mm ean 29191

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Extra robust and solid elastic non-marking grey rubber Wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Product line: Rubber tyre

EAN13:8018793291910 **EAN5:**29191 **Article code:**146040045712G



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	457
Band width (mm)	122
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1400
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/