

SERIE 115

118XBIS

AVO - Wheel with phenolic resin and aisi 304 stainless steel castor for industry, diameter 200mm ean 28855

Material: Phenolic resin

Core: Phenolic resin

Application field: Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

Heavy-Duty Castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and rear brake. Dust cover ring on the balls.

Product line: High temperature, Stainless steel

EAN13:8018793288552 **EAN5:**28855 **Article code:**06118XF2000FN



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 600 DaN

- Concrete

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

- Stoneware

Flooring

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	600
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel