

SERIE 115

117BISANT

AVO - Wheel with phenolic resin and steel castor for industry, diameter 125mm ean 28695

Material: Phenolic resin

Core: Phenolic resin

Application field:
Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel. Stainless steel Teflon bush available on request.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: High temperature, Stainless steel

EAN13:8018793286954

EAN5:28695

Article code:05117S0A121FN



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 170 DaN

- Concrete
- Stoneware

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	153
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized