

SERIE 116BU

125A-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 160mm ean 28793

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel, Polyamide

EAN13:8018793287937 **EAN5:**28793 **Article code:**06125XA1600FB



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 450 DaN

Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	450
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	216
Castor hole (mm)	/
Static load capacity (DaN)	560
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel