

SERIE 116BU

125A-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 28796

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel, Polyamide

EAN13:8018793287968 **EAN5:**28796 **Article code:**06125XA2000RB



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 600 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	600
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel