

SERIE 116N

97XA

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 28822

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel, Polyamide

EAN13:8018793288224 **EAN5:**28822 **Article code:**0697XA02000RN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 600 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|--------------------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 50 |
| Hub width (mm) | 58 |
| Hub version | Stainless steel roller bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 600 |
| Colour | Black |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 135X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | / |
| Ground clearance (mm) | 251 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 750 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |