

SERIE 116G

119BG

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 80mm ean 28198

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem.

Product line: Stainless steel, Polyamide

EAN13:8018793281980 **EAN5:**28198 **Article code:**06119B00800FG



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 150 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------|
| Diameter (mm) | 80 |
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 150 |
| Colour | Green |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|--|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 105 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 190 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Plain axle | 20X50 |
| Stem type | Plain axle Stem (on request threaded stem) |
| Finishing | AISI 304 stainless steel |