

SERIE 116-PS

137BIS-PA

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 100mm ean 28262

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:


Heavy polyamide 6 wheel. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Polyamide

EAN13:8018793282628 **EAN5:**28262 **Article code:**051370F102SCN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 1000 DaN
Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11
Offset (mm)	55
Ground clearance (mm)	148
Castor hole (mm)	/
Static load capacity (DaN)	1250
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Black painted