

SERIE 116G

# 118BISANTFG

AVO - Wheel with polyamide 6 and steel castor for industry,  
diameter 150mm ean 28163

**Material:** Polyamide 6    **Core:** Polyamide 6    **Scope:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793281638    **EAN5:**28163    **Article code:**05118SFA150FG



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 200 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Green
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	12
Static load capacity (DaN)	250
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized