

SERIE 116N-P

137BIS-N

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 200mm ean 27850

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Heavy monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Polyamide

EAN13:8018793278508 **EAN5:**27850 **Article code:**05137N0F200CN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 1600 DaN
Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	57
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1600
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	270
Castor hole (mm)	/
Static load capacity (DaN)	2000
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Black painted