

SERIE 116

118F

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 200mm ean 28500

Material:
Polyamide 6

Core: Conductive
polyamide 6

Application field:
Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793285001 **EAN5:**28500 **Article code:**C5118F02000CN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 550 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	550
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	690
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized