

SERIE 112

103B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 100mm

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**03103B01005RN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 70 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	8X30
Stem type	Plain axle
Finishing	Galvanized