

SERIE 112B

## 407SEP-SSX

**AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 125mm ean 24874**

**Material:** Solid Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with container plate fitting (left version) . Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793248747

**EAN5:**24874

**Article code:**02407SS127PBN



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 100 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                   |
|-----------------------------|-------------------|
| Diameter (mm)               | 125               |
| Band width (mm)             | 38                |
| Hub width (mm)              | 50                |
| Hub version                 | Plain bore        |
| Wheel hole (mm)             | 15                |
| Bearing seat (mm)           | /                 |
| Dynamic load capacity (DaN) | 100               |
| Colour                      | Black             |
| Material                    | Solid Rubber tyre |
| Box pieces                  | /                 |
| Hardness scale              | Shore A           |
| Hardness                    | 83                |

## Support data

|                            |                   |
|----------------------------|-------------------|
| Plate size (mm)            | 100X085           |
| Plate hole spacing (mm)    | 080X060           |
| Plate hole size (mm)       | 8,5X12            |
| Offset (mm)                | 42                |
| Ground clearance (mm)      | 155               |
| Castor hole (mm)           | /                 |
| Static load capacity (DaN) | 130               |
| Structure                  | Swivel            |
| Version                    | Container fitting |
| Brake                      | /                 |
| Plain axle                 | /                 |
| Stem type                  | /                 |
| Finishing                  | Galvanized        |