

SERIE 112B

407SEP-SDX

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 125mm ean 24875

Material: Solid Rubber
tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with container plate fitting (right version) . Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793248754

EAN5:24875

Article code:02407SD127PBN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 100 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Container fitting
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized