

SERIE 112B

90STAR

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 150mm

Material: Solid Rubber
tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**0290STAR150RN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	90STAR
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized