

SERIE 604

607

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 306mm ean 28510

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Rubber tyre, Pneumatic

EAN13:8018793285100 **EAN5:**28510 **Article code:**2160700306093



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1100 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	306
Band width (mm)	93
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	1100
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	90
Ground clearance (mm)	376
Castor hole (mm)	/
Static load capacity (DaN)	1300
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted