

SERIE 112-M78

112-M78

**AVO - Wheel with solid rubber tyre for industry, diameter 380mm
ean 17193**

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Solid rubber wheel with steel flanges and hub on plain bore, designed for use on cement mixers, construction machinery and site equipment, where strength, stability and long service life are required. The high-quality solid rubber tread ensures good shock absorption, excellent ground adhesion and smooth rolling performance, even on uneven or rough surfaces.

Product line: Rubber tyre

EAN13: 8018793171939 **EAN5:** 17193 **Article code:** 03112783808BN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	380
Band width (mm)	80
Hub width (mm)	78
Hub version	Plain bore
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/