

SERIE 17

32X

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 150mm ean 28740

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793287401

EAN5:28740

Article code:06032X0150NBA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 450 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	60
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	450
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	201
Castor hole (mm)	/
Static load capacity (DaN)	560
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel