

SERIE 17G-S

## 32XG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 150mm ean 28749

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793287494 **EAN5:**28749 **Article code:**06832X0150NBG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 450 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	60
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	450
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	201
Castor hole (mm)	/
Static load capacity (DaN)	560
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel