

SERIE 61

# 432XBIS

**AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 150mm ean 28808**

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and rear brake. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793288088    **EAN5:**28808    **Article code:**06432XF150NBA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 450 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 150                        |
| Band width (mm)             | 40                         |
| Hub width (mm)              | 60                         |
| Hub version                 | Plain bore                 |
| Wheel hole (mm)             | 20                         |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 450                        |
| Colour                      | Blue                       |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | 135X110                  |
| Plate hole spacing (mm)    | 105X080                  |
| Plate hole size (mm)       | 13X16                    |
| Offset (mm)                | 57                       |
| Ground clearance (mm)      | 201                      |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 560                      |
| Structure                  | Swivel                   |
| Version                    | Plate with brake         |
| Brake                      | Rear                     |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |