

SERIE 17

## 331XANT-AVO

AVO - Wheel with thermoplastic polyurethane and aisi 316 stainless steel castor for industry, diameter 60mm ean 23710

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed steel AISI 316, turning on double rim of stainless-steel balls AISI 316, with plate and front brake.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793237109    **EAN5:**23710    **Article code:**A63310A060NBX



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 60                         |
| Band width (mm)             | 35                         |
| Hub width (mm)              | 40                         |
| Hub version                 | Plain bore                 |
| Wheel hole (mm)             | 12                         |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 70                         |
| Colour                      | Red                        |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

### Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | 100X085                  |
| Plate hole spacing (mm)    | 080X060                  |
| Plate hole size (mm)       | 8,5X12                   |
| Offset (mm)                | 42                       |
| Ground clearance (mm)      | 89                       |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 100                      |
| Structure                  | Swivel                   |
| Version                    | Plate with brake         |
| Brake                      | Front                    |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | Aisi 316 stainless steel |