

SERIE 17

# 331XANTF-AVO

AVO - Wheel with thermoplastic polyurethane and aisi 316 stainless steel castor for industry, diameter 60mm ean 24292

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 316, turning on double rim of balls AISI 316, with bolt hole and front brake.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793242929    **EAN5:**24292    **Article code:**A6331FA060NBX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 100 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	60
Band width (mm)	35
Hub width (mm)	30
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	87
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel