

SERIE 17G-S

## 31BG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 27515

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793275156 **EAN5:**27515 **Article code:**12831B0150NCG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 200 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle
Finishing	Galvanized