

SERIE 21

72

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 28414

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793284141

EAN5:28414

Article code:2107200160OCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	Ochre
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	1250
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted