

SERIE 21-S

72A-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 28420

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyurethane

EAN13: 8018793284202

EAN5: 28420

Article code: 21072A0160BCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	/
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	1250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted