

SERIE 17

31X

AVO - Wheel with thermoplastic polyurethane for industry, diameter 160mm ean 28680

Material: Thermoplastic Polyurethane **Core:** Polyamide 6 **Application field:** Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Product line: Polyurethane, Stainless steel

EAN13:8018793286800 **EAN5:**28680 **Article code:**06831XF160NCG

Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	55
Hub version	Stainless steel ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	197
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	/
Brake	Front
Plain axle	/
Stem type	/
Finishing	/