Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

# **109BIS**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 100mm ean 22167

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

#### **Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

**EAN13**:8018793221672 **EAN5**:22167 **Article code**:041090F1000GP



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 300 DaN • Asphalt

Rotation: Ball bearing Hardness scale: HB Hardness: 200

Concrete

### Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11
Offset (mm)	36
Ground clearance (mm)	150
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	1
Finishing	Black painted